


MATCH NEW PAVEMENT INTO EXISTING BOAT RAMP.
PROVIDE CONCRETE EDGE BEAM AT ASPHALT-CONCRETE INTERFACE

MATCH NEW PAVEMENT INTO EXISTING RAMP

MATCH NEW PAVEMENT INTO EXISTING PAVEMENT.
PROFILE EXISTING ASPHALT FOR 1m BEYOND LIMIT OF
WORKS AND EXTEND NEW PAVEMENT ASPHALT LAYER

Original Size:
1:500
1:1000 (A3)



ROADING & PAVEMENT NOTES:

1. THESE DRAWINGS SHOULD BE READ IN CONJUNCTION WITH THE HARD SURFACE LANDSCAPING DRAWINGS PREPARED BY BOFFA MISKELL.
2. MINIMUM CONCRETE STRENGTHS AT 28 DAYS SHALL BE AS FOLLOWS:
 - 25MPa FOR VEHICLE PAVEMENTS
 - 20MPa FOR PEDESTRIAN PAVEMENTS
3. AFTER BULK EXCAVATION HAS BEEN COMPLETED THE PAVEMENT SUBGRADE SURFACE SHOULD BE PROOF ROLLED. ANY SOFT, WET OR UNSUITABLE MATERIALS SHALL BE REMOVED AND REPLACED WITH AN APPROVED GRANULAR MATERIAL (MIN. CBR 10).
4. RECYCLED MATERIALS SHALL BE UTILISED IN PAVEMENT CONSTRUCTION AS MUCH AS PRACTICABLE. EXAMPLES INCLUDE CRUSHED CONCRETE IN PLACE OF GAP20, GAP40 & GAP65.

No.	Revision Details	(Current Revision Date : 27/04/2021)	Date
B	RC S92 ISSUE		20/05/21
A	ISSUED FOR RESOURCE CONSENT		19/02/21

Design	AW
Survey	
Drawn	MK
Checked	ML
Date	27/04/2021
Scale	1:500 (A1) 1:1000 (A3)
CAD Filename	12582-01-300.dwg
© Copyright 2021 Airey Consultants Ltd	


Job Title:
BAYSWATER MARINA HOLDINGS LTD
BAYSWATER MARITIME PRECINCT
21 SIR PETER BLAKE PARADE
BAYSWATER
AUCKLAND



Drawing Title: PROPOSED ROADING	
File No. 12582-01-300	Rev. B
Dwg. No. 300	



Original Size:
 1:250
 1:500 (A3)



ROADING & PAVEMENT NOTES:

1. THESE DRAWINGS SHOULD BE READ IN CONJUNCTION WITH THE HARD SURFACE LANDSCAPING DRAWINGS PREPARED BY BOFFA MISKELL.
2. MINIMUM CONCRETE STRENGTHS AT 28 DAYS SHALL BE AS FOLLOWS:
 - 25MPa FOR VEHICLE PAVEMENTS
 - 20MPa FOR PEDESTRIAN PAVEMENTS
3. AFTER BULK EXCAVATION HAS BEEN COMPLETED THE PAVEMENT SUBGRADE SURFACE SHOULD BE PROOF ROLLED. ANY SOFT, WET OR UNSUITABLE MATERIALS SHALL BE REMOVED AND REPLACED WITH AN APPROVED GRANULAR MATERIAL (MIN. CBR 10).
4. RECYCLED MATERIALS SHALL BE UTILISED IN PAVEMENT CONSTRUCTION AS MUCH AS PRACTICABLE. EXAMPLES INCLUDE CRUSHED CONCRETE IN PLACE OF GAP20, GAP40 & GAP65.

No.	Revision Details	Date
B	RC S92 ISSUE	20/05/21
A	ISSUED FOR RESOURCE CONSENT	19/02/21
(Current Revision Date : 27/04/2021)		

Design AW
 Survey
 Drawn MK
 Checked ML
 Date 27/04/2021
 Scale 1:250 (A1) 1:500 (A3)
 CAD Filename 12582-01-300.dwg
 © Copyright 2021 Airey Consultants Ltd



Job Title:
BAYSWATER MARINA HOLDINGS LTD
BAYSWATER MARITIME PRECINCT
21 SIR PETER BLAKE PARADE
BAYSWATER
AUCKLAND



Drawing Title:
PROPOSED ROADING 1 OF 4


File No.
12582-01-300

Rev.
B

Dwg. No.
301



Original Size:
1:250
1:500 (A3)



ROADING & PAVEMENT NOTES:

1. THESE DRAWINGS SHOULD BE READ IN CONJUNCTION WITH THE HARD SURFACE LANDSCAPING DRAWINGS PREPARED BY BOFFA MISKELL.
2. MINIMUM CONCRETE STRENGTHS AT 28 DAYS SHALL BE AS FOLLOWS:
 - 25MPa FOR VEHICLE PAVEMENTS
 - 20MPa FOR PEDESTRIAN PAVEMENTS
3. AFTER BULK EXCAVATION HAS BEEN COMPLETED THE PAVEMENT SUBGRADE SURFACE SHOULD BE PROOF ROLLED. ANY SOFT, WET OR UNSUITABLE MATERIALS SHALL BE REMOVED AND REPLACED WITH AN APPROVED GRANULAR MATERIAL (MIN. CBR 10).
4. RECYCLED MATERIALS SHALL BE UTILISED IN PAVEMENT CONSTRUCTION AS MUCH AS PRACTICABLE. EXAMPLES INCLUDE CRUSHED CONCRETE IN PLACE OF GAP20, GAP40 & GAP65.

No.	Revision Details	(Current Revision Date : 27/04/2021)	Date
B	RC S92 ISSUE		20/05/21
A	ISSUED FOR RESOURCE CONSENT		19/02/21

Design	AW
Survey	
Drawn	MK
Checked	ML
Date	27/04/2021
Scale	1:250 (A1) 1:500 (A3)
CAD Filename	12582-01-300.dwg
© Copyright 2021 Airey Consultants Ltd	


Job Title:
BAYSWATER MARINA HOLDINGS LTD
BAYSWATER MARITIME PRECINCT
21 SIR PETER BLAKE PARADE
BAYSWATER
AUCKLAND



Drawing Title: PROPOSED ROADING 2 OF 4	
File No. 12582-01-300	Rev. B
Dwg. No. 302	



Original Size:
1:250
1:500 (A3)



ROADING & PAVEMENT NOTES:

1. THESE DRAWINGS SHOULD BE READ IN CONJUNCTION WITH THE HARD SURFACE LANDSCAPING DRAWINGS PREPARED BY BOFFA MISKELL.
2. MINIMUM CONCRETE STRENGTHS AT 28 DAYS SHALL BE AS FOLLOWS:
 - 25MPa FOR VEHICLE PAVEMENTS
 - 20MPa FOR PEDESTRIAN PAVEMENTS
3. AFTER BULK EXCAVATION HAS BEEN COMPLETED THE PAVEMENT SUBGRADE SURFACE SHOULD BE PROOF ROLLED. ANY SOFT, WET OR UNSUITABLE MATERIALS SHALL BE REMOVED AND REPLACED WITH AN APPROVED GRANULAR MATERIAL (MIN. CBR 10).
4. RECYCLED MATERIALS SHALL BE UTILISED IN PAVEMENT CONSTRUCTION AS MUCH AS PRACTICABLE. EXAMPLES INCLUDE CRUSHED CONCRETE IN PLACE OF GAP20, GAP40 & GAP65.

No.	Revision Details	Date
B	RC S92 ISSUE	20/05/21
A	ISSUED FOR RESOURCE CONSENT	19/02/21
(Current Revision Date : 27/04/2021)		

Design	AW
Survey	
Drawn	MK
Checked	ML
Date	27/04/2021
Scale	1:250 (A1) 1:500 (A3)
CAD Filename	12582-01-300.dwg
© Copyright 2021 Airey Consultants Ltd	

Job Title:
BAYSWATER MARINA HOLDINGS LTD
BAYSWATER MARITIME PRECINCT
21 SIR PETER BLAKE PARADE
BAYSWATER
AUCKLAND



Drawing Title: PROPOSED ROADING 3 OF 4		
File No. 12582-01-300	Rev. B	Dwg. No. 303